

# AASHTO M-288 RECOMMENDED PRODUCTS

Application	Class		Nonwoven	Woven
Subsurface Drainage	Class 1	≤15% <i>in Situ</i> Soil passing 0.075 mm	Geotex 801	Geotex 2x2HF
		15 to 50% <i>in Situ</i> Soil passing 0.075 mm	Geotex 801	-
		>50% <i>in Situ</i> Soil passing 0.075 mm	Geotex 801	-
	Class 2	≤15% <i>in Situ</i> Soil passing 0.075 mm	Geotex 601	-
		15 to 50% <i>in Situ</i> Soil passing 0.075 mm	Geotex 601	Geotex 104F
		>50% <i>in Situ</i> Soil passing 0.075 mm	Geotex 601	Geotex 104F
	Class 3 (Use Class 3 only if specified by engineer – see note b of table 2 in M288 spec)	≤15% <i>in Situ</i> Soil passing 0.075 mm	Geotex 401	-
		15 to 50% <i>in Situ</i> Soil passing 0.075 mm	Geotex 401	-
		>50% <i>in Situ</i> Soil passing 0.075 mm	Geotex 401	-
Separation	Class 1		Geotex 801	Geotex 315ST
	Class 2		Geotex 601	Geotex 250ST
	Class 3		Geotex 401	Geotex 200ST
Stabilization	Class 1		Geotex 801	Geotex 315ST
	Class 2 (Use class 2 only if specified by engineer – see note a of table 5 in M288 spec)		Geotex 601	Geotex 250ST
	Class 3 (Use class 3 only if specified by engineer – see note a of table 5 in M288 spec)		Geotex 401	Geotex 200ST
Permanent Erosion Control	Class 1 (Geotextiles other than woven monofilaments)	≤15% <i>in Situ</i> Soil passing 0.075 mm	Geotex 801	Geotex 2x2HF
		15 to 50% <i>in Situ</i> Soil passing 0.075 mm	Geotex 801	-
		>50% <i>in Situ</i> Soil passing 0.075 mm	Geotex 801	-
	Class 2 (Woven Monofilament Geotextiles or other geotextiles as specified by engineer - see note c of table 6 in M288 specs)	≤15% <i>in Situ</i> Soil passing 0.075 mm	Geotex 601	Geotex 104F
		15 to 50% <i>in Situ</i> Soil passing 0.075 mm	Geotex 601	-
		>50% <i>in Situ</i> Soil passing 0.075 mm	Geotex 601	-
Temporary Silt Fence	Supported		Geotex 351	-
	Unsupported		-	Geotex 2130
Paving Fabric	-		Petromat 4598	-